## NSN 5950-00-645-9133

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-9133

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.234 inches single mounting facility single center group and 2.266 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.109 inches single mounting facility single center group and 2.141 inches single mounting facility single center group

### **Overall Height:**

Between 4.234 inches and 4.266 inches

### **Inductance Type:**

Fixed

### **Inductance Rating:**

10.00 henry single component single winding

#### Frequency Rating:

120.0 hertz single component

### **Body Length:**

3.000 inches

### **Body Width:**

Between 2.859 inches and 2.891 inches

### **Body Height:**

Between 3.734 inches and 3.766 inches

### **Winding Quantity:**

1 single component

### Inclosure Type:

Fully enclosed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded hole single group

### Rating Method:

Electrical single component single winding

### Thready Qty Per Inch (tpi):

32 single group

### **Thread Size:**

0.164 inches single group

### **Winding Operating Current:**

125.0 milliamperes dc single component single winding

### Dc Resistance Rating In Ohms:

150.000 single component single winding

### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

2 tab, solder lug

# NSN 5950-00-645-9133

Reactor - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0