## NSN 5950-00-645-9139

Reactor - Page 1 of 2

Reliability Indicator:

**Special Features:**Solder lug ground term



View Online at https://aerobasegroup.com/nsn/5950-00-645-9139

Not established
Turn Quantity:
2268 single component single winding
Center To Center Distance Between Mounting Facilities Parallel To Length
1.375 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.500 inches single mounting facility single center group
Overall Height:
3.750 inches
Inductance Type:
Fixed
Inductance Rating:
8.00 henry single component single winding
Frequency Rating:
120.0 hertz single component
Body Length:
2.000 inches
Body Width:
2.125 inches
Body Height:
3.250 inches
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Rating Method:
Electrical single component single winding
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.164 inches single group
Winding Operating Current:
100.0 milliamperes dc single component single winding
Dc Resistance Rating In Ohms:
150.000 single component single winding

## **NSN 5950-00-645-9139** Reactor - Page 2 of 2



inread Series Designator:
Unc single group
Terminal Type And Quantity:
2 standoff insulator and 1 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A058b0