

View Online at <https://aerobasegroup.com/nsn/5950-00-645-9383>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.440 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.440 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

5.340 inches

Body Width:

4.840 inches

Body Height:

6.120 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

30.0 amperes ac single component single secondary

Winding Operating Voltage:

6.30 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0