

View Online at <https://aerobasegroup.com/nsn/5950-00-645-9706>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

5.125 inches single mounting facility single center group

Mounting Hole Diameter:

0.625 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

7.375 inches

Body Width:

7.062 inches

Body Height:

8.125 inches

End Application:

Arsr-1, fa-7148 transmitter modulator cabinet

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Current:

33.0 amperes ac single component 4th secondary

Winding Operating Voltage:

5.00 ac pounds per hour wet single component all secondary

Special Features:

Function, tranformer, power, step-down; reference data, t-102, instruction book, arsr-1d/e/f, vol 5, sec 10, pg 10-40

Terminal Type And Quantity:

2 solder stud and 6 standoff, threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0