# NSN 5950-00-645-9706

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-9706

# Reliability Indicator:

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

6.375 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

5.125 inches single mounting facility single center group

## **Mounting Hole Diameter:**

0.625 inches single group

#### Frequency Rating:

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

#### **Body Length:**

**7.375** inches

**Body Width:** 

7.062 inches

#### **Body Height:**

8.125 inches

# **End Application:**

Arsr-1, fa-7148 transmitter modulator cabinet

#### **Inclosure Type:**

Fully enclosed

# **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Flange single group and unthreaded hole single group

## **Winding Function And Quantity:**

1 primary single component and 4 secondary single component

# **Winding Operating Current:**

33.0 amperes ac single component 4th secondary

# **Winding Operating Voltage:**

5.00 ac pounds per hour wet single component all secondary

#### **Special Features:**

Function, tranformer, power, step-down; reference data, t-102, instruction book, arsr-1d/e/f, vol 5, sec 10, pg 10-40

# **Terminal Type And Quantity:**

2 solder stud and 6 standoff, threaded stud

# Shelf Life:

N/a

## **Unit Of Measure:**

--

# NSN 5950-00-645-9706

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0