## NSN 5950-00-645-9786

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-645-9786

| Reliability Indicator:   |
|--|
| Not established  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:  |
| 3.500 inches single mounting facility single center group  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:   |
| 2.250 inches single mounting facility single center group  |
| Inductance Type:   |
| Fixed  |
| Inductance Rating:   |
| 12.00 henry single component single winding  |
| Body Length:   |
| 4.250 inches   |
| Body Width:  |
| 3.250 inches   |
| Body Height:   |
| 3.000 inches   |
| Winding Quantity:  |
| 1 single component   |
| Inclosure Type:  |
| Hermetically sealed  |
| Mounting Facility Quantity:  |
| 6 single group   |
| Mounting Method:   |
| Flange single group and unthreaded hole single group   |
|  |
| Winding Operating Current:   |
| Winding Operating Current:  150.0 milliamperes dc single component single winding  |
|  |
| 150.0 milliamperes dc single component single winding  |
| 150.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:   |
| 150.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  150.000 single component single winding  |
| 150.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  150.000 single component single winding  Special Features:   |
| 150.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  150.000 single component single winding  Special Features:  2.5 kv rms test voltage, case metal material; 2 rows of mtg holes each spaced 1.125 in. C to c   |
| 150.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  150.000 single component single winding  Special Features:  2.5 kv rms test voltage, case metal material; 2 rows of mtg holes each spaced 1.125 in. C to c  Terminal Type And Quantity:  |
| 150.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  150.000 single component single winding  Special Features:  2.5 kv rms test voltage, case metal material; 2 rows of mtg holes each spaced 1.125 in. C to c  Terminal Type And Quantity:  2 tab, solder lug   |
| 150.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  150.000 single component single winding  Special Features:  2.5 kv rms test voltage, case metal material; 2 rows of mtg holes each spaced 1.125 in. C to c  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  |
| 150.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  150.000 single component single winding  Special Features:  2.5 kv rms test voltage, case metal material; 2 rows of mtg holes each spaced 1.125 in. C to c  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a                                       |
| 150.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  150.000 single component single winding  Special Features:  2.5 kv rms test voltage, case metal material; 2 rows of mtg holes each spaced 1.125 in. C to c  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a                                       |
| 150.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  150.000 single component single winding  Special Features:  2.5 kv rms test voltage, case metal material; 2 rows of mtg holes each spaced 1.125 in. C to c  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:                     |
| 150.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  150.000 single component single winding  Special Features:  2.5 kv rms test voltage, case metal material; 2 rows of mtg holes each spaced 1.125 in. C to c  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization: |