NSN 5950-00-645-9824

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-9824

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.250 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.875 inches single mounting facility single center group |
| Inductance Type: |
| Swinging |
| Frequency Rating: |
| 1.6 kilohertz single component |
| Body Length: |
| 1.640 inches |
| Body Width: |
| 1.270 inches |
| Body Height: |
| 2.520 inches |
| Maximum Operating Temp: |
| 130.0 degrees celsius |
| Winding Quantity: |
| 6 single component |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Rating Method: |
| Electrical single component single winding |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Conductor Size: |
| 0.02535 inches american wire gage single component all winding |
| Winding Operating Current: |
| 2.0 milliamperes dc single component single winding |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 12 tab, solder lug |
| Shelf Life: |

N/a

NSN 5950-00-645-9824

Reactor - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A058b0