## NSN 5950-00-645-9824

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-9824

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.250 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 0.875 inches single mounting facility single center group                 |
| Inductance Type:  |
| Swinging  |
| Frequency Rating:   |
| 1.6 kilohertz single component  |
| Body Length:  |
| 1.640 inches  |
| Body Width:   |
| 1.270 inches  |
| Body Height:  |
| 2.520 inches  |
| Maximum Operating Temp:   |
| 130.0 degrees celsius   |
| Winding Quantity:   |
| 6 single component  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Rating Method:  |
| Electrical single component single winding                                |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.138 inches single group   |
| Winding Conductor Size:   |
| 0.02535 inches american wire gage single component all winding            |
| Winding Operating Current:  |
| 2.0 milliamperes dc single component single winding                       |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 12 tab, solder lug  |
| Shelf Life:   |

N/a

## NSN 5950-00-645-9824

Reactor - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A058b0