

View Online at <https://aerobasegroup.com/nsn/5950-00-646-1218>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.562 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 3.907 inches and 4.032 inches

Body Width:

Between 3.281 inches and 3.406 inches

Body Height:

Between 6.093 inches and 6.281 inches

Inclosure Type:

Fully enclosed with oil

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 7 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

2.0 amperes ac single component 4th secondary

Winding Power Rating:

10.0 volts-amperes single component 3rd secondary

Winding Operating Voltage:

5.00 ac volts single component 3rd secondary

Special Features:

1 primary winding; 7 secondary windings

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

20 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0