

View Online at <https://aerobasegroup.com/nsn/5950-00-646-1218>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.125 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.562 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:**

Between 3.907 inches and 4.032 inches

**Body Width:**

Between 3.281 inches and 3.406 inches

**Body Height:**

Between 6.093 inches and 6.281 inches

**Inclosure Type:**

Fully enclosed with oil

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 7 secondary single component

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

2.0 amperes ac single component 4th secondary

**Winding Power Rating:**

10.0 volts-amperes single component 3rd secondary

**Winding Operating Voltage:**

5.00 ac volts single component 3rd secondary

**Special Features:**

1 primary winding; 7 secondary windings

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

20 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0