## NSN 5950-00-646-1262

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-646-1262
Reliability Indicator: Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.625 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.750 inches single mounting facility single center group
Mounting Hole Diameter:
0.198 inches single group and 0.205 inches single group
Frequency Rating:
380.0 hertz single component and 1.0 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure and core single component
Body Length:
2.680 inches
Body Width:
2.620 inches
Body Height:
2.560 inches
Inclosure Type:
Partially enclosed, double shell
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
11.1 amperes ac single component single secondary and 13.4 amperes ac single component single secondary and 14.2 amperes ac single
component single secondary
Winding Operating Voltage:
8.40 ac volts single component single secondary and 11.00 ac volts single component single secondary and 12.10 ac volts single
component single secondary
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig: A058b0

No