

View Online at <https://aerobasegroup.com/nsn/5950-00-646-1262>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches single mounting facility single center group

Mounting Hole Diameter:

0.198 inches single group and 0.205 inches single group

Frequency Rating:

380.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

2.680 inches

Body Width:

2.620 inches

Body Height:

2.560 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

11.1 amperes ac single component single secondary and 13.4 amperes ac single component single secondary and 14.2 amperes ac single component single secondary

Winding Operating Voltage:

8.40 ac volts single component single secondary and 11.00 ac volts single component single secondary and 12.10 ac volts single component single secondary

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0