## NSN 5950-00-646-1799

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-646-1799

| Deliahilita ladioatea   |
|---|
| Reliability Indicator:  |
| Not established   |
| Turn Quantity:  |
| 23 single component single winding  |
| Inductance Rating:  |
| 2.50 microhenries single component single winding and 3.30 microhenries single component single winding |
| Coil Form Type:   |
| Hollow single component   |
| Core Construction:  |
| Powdered single component   |
| Adjustment Device Drive Type:   |
| Slotted screw single component  |
| Body Length:  |
| 0.844 inches  |
| Body Outside Diameter:  |
| 0.250 inches  |
| Overall Diameter:   |
| 0.344 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Threaded bushing single group   |
| Rating Method:  |
| Electrical single component single winding and winding turns single component single winding            |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.164 inches single group   |
| Winding Conductor Size:   |
| 0.01003 inches american wire gage single component single winding                                       |
| Quality Factor:   |
| 35 single component single winding and 45 single component single winding                               |
| Adjustment Method And Quantity:   |
| 1 adjustable core single component  |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 2 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5950-00-646-1799

Radio Frequency Coil - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0