NSN 5950-00-646-2034

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-646-2034

Reliability	Indicator:
-------------	------------

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.938 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.250 inches

Body Width:

1.750 inches

Body Height:

2.406 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Winding Operating Current:

1.0 amperes ac single component 3rd secondary

Winding Operating Voltage:

5.80 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-00-646-2034

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0