

View Online at <https://aerobasegroup.com/nsn/5950-00-646-2039>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.985 inches single mounting facility single center group and 3.015 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.485 inches single mounting facility single center group and 2.515 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

Between 3.970 inches and 4.030 inches

**Body Width:**

Between 3.345 inches and 3.405 inches

**Body Height:**

Between 4.970 inches and 5.030 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 5 secondary single component

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

0.9 amperes ac single component 4th secondary

**Winding Power Rating:**

5.67 volts-amperes single component 4th secondary

**Winding Operating Voltage:**

6.30 ac volts single component all secondary

**Special Features:**

1 primary winding; 5 secondary windings

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

13 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0