

View Online at <https://aerobasegroup.com/nsn/5950-00-646-2039>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.985 inches single mounting facility single center group and 3.015 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.485 inches single mounting facility single center group and 2.515 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 3.970 inches and 4.030 inches

Body Width:

Between 3.345 inches and 3.405 inches

Body Height:

Between 4.970 inches and 5.030 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

0.9 amperes ac single component 4th secondary

Winding Power Rating:

5.67 volts-amperes single component 4th secondary

Winding Operating Voltage:

6.30 ac volts single component all secondary

Special Features:

1 primary winding; 5 secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0