NSN 5950-00-646-2073

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-646-2073

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.687 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

320.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.062 inches

Body Width:

2.000 inches

Body Height:

2.219 inches

Maximum Operating Temp:

180.0 degrees celsius

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

5.0 amperes ac single component 1st secondary

Winding Operating Voltage:

6.30 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

NSN 5950-00-646-2073Power Transformer - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

Demilitarization:

No

Fiig:

A058b0