# NSN 5950-00-646-2101

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-646-2101

#### **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

13.250 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

4.250 inches single mounting facility single center group

#### Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

#### **Transformer Winding Connection Type:**

Delta-delta

#### **Maximum Transformer Power Rating:**

1.0 kilovolt-ampere single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure single component

#### **Body Length:**

13.938 inches

#### **Body Width:**

10.500 inches

#### **Body Height:**

9.625 inches

#### **Inclosure Type:**

Hermetically sealed

#### **Mounting Facility Quantity:**

6 single group

## **Mounting Method:**

Threaded hole single group

## Winding Function And Quantity:

1 primary single component and 1 secondary single component

#### **Thread Size:**

0.312 inches single group

## **Winding Operating Current:**

195.0 milliamperes ac single component single secondary

#### **Winding Operating Voltage:**

9400.00 ac volts single component single secondary

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

6 standoff, solder lug

## Shelf Life:

N/a

# **NSN 5950-00-646-2101**Power Transformer - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

Demilitarization:

No

Fiig:

A058b0