

View Online at <https://aerobasegroup.com/nsn/5950-00-646-2432>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.745 inches single mounting facility single center group and 4.755 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.495 inches single mounting facility single center group and 2.505 inches single mounting facility single center group

Mounting Hole Diameter:

0.225 inches single group and 0.235 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 5.515 inches and 5.525 inches

Body Width:

Between 4.555 inches and 4.565 inches

Body Height:

Between 5.297 inches and 5.327 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

1.2 amperes ac single component single secondary

Winding Power Rating:

130.0 volts-amperes single component single secondary

Winding Operating Voltage:

50.00 ac volts single component single secondary and 65.00 ac volts single component single secondary and 80.00 ac volts single component single secondary and 100.00 ac volts single component single secondary and 115.00 ac volts single component single secondary and 130.00 ac volts single component single secondary

Terminal Type And Quantity:

10 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0