## NSN 5950-00-646-2432

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-646-2432

#### **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

4.745 inches single mounting facility single center group and 4.755 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.495 inches single mounting facility single center group and 2.505 inches single mounting facility single center group

#### **Mounting Hole Diameter:**

0.225 inches single group and 0.235 inches single group

#### Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Body Length:**

Between 5.515 inches and 5.525 inches

#### **Body Width:**

Between 4.555 inches and 4.565 inches

#### **Body Height:**

Between 5.297 inches and 5.327 inches

#### **Maximum Operating Temp:**

105.0 degrees celsius

## Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

6 single group

#### **Mounting Method:**

Unthreaded hole single group

## **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

#### **Winding Operating Current:**

1.2 amperes ac single component single secondary

## Winding Power Rating:

130.0 volts-amperes single component single secondary

#### Winding Operating Voltage:

50.00 ac volts single component single secondary and 65.00 ac volts single component single secondary and 80.00 ac volts single component single secondary and 115.00 ac volts single component single secondary and 130.00 ac volts single component single secondary

#### **Terminal Type And Quantity:**

10 threaded stud

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

#### **Demilitarization:**

No

# NSN 5950-00-646-2432

Power Transformer - Page 2 of 2



Fiig:

A058b0