# NSN 5950-00-646-2470

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-646-2470

# **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.438 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.500 inches single mounting facility single center group

#### **Overall Height:**

6.375 inches

#### **Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

#### **Body Length:**

Between 4.531 inches and 4.656 inches

#### **Body Width:**

Between 3.375 inches and 3.500 inches

#### **Body Height:**

Between 5.250 inches and 5.438 inches

# Inclosure Type:

Hermetically sealed

#### **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded stud single group

# **Winding Function And Quantity:**

1 primary single component and 4 secondary single component

#### Thready Qty Per Inch (tpi):

20 single group

#### **Thread Size:**

0.250 inches single group

# **Winding Operating Current:**

4.5 amperes ac single component 3rd secondary

# **Winding Operating Voltage:**

6.40 ac volts single component all secondary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

12 standoff, solder lug

# Shelf Life:

N/a

# **NSN 5950-00-646-2470**Power Transformer - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

Demilitarization:

No

Fiig:

A058b0