## NSN 5950-00-646-2576

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-646-2576

Reliability Indicator:
Not established
Overall Length:
5.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.062 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.950 inches single mounting facility single center group and 3.046 inches single mounting facility single center group
Overall Height:
3.687 inches
Overall Width:
3.875 inches
Frequency Rating:
380.0 hertz single component and 1.6 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to core single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 2 secondary single component
Thread Size:
0.164 inches single group
Winding Operating Current:
95.0 milliamperes ac single component 2nd secondary
Winding Power Rating:
327.6 volts-amperes single component 1st secondary
Winding Operating Voltage:
115.00 ac volts single component single primary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
14 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

## NSN 5950-00-646-2576

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0