NSN 5950-00-646-2814

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-646-2814

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 6.938 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.250 inches single mounting facility single center group |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 8.750 inches |
| Body Width: |
| 4.438 inches |
| Body Height: |
| 5.250 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange and slot single group |
| Winding Function And Quantity: |
| 1 primary and 1 secondary single component |
| Winding Operating Current: |
| 30.0 milliamperes dc single component single secondary |
| Winding Operating Voltage: |
| 115.00 ac volts single component single primary |
| Special Features: |
| Case metal material; 1.688 in. O/a height of standoff type terminals |
| Terminal Type And Quantity: |
| 2 wire lead and 2 standoff, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |