## NSN 5950-00-646-2901

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-646-2901

| Reliability Indicator:   |
|--|
| Not established  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                                      |
| 2.000 inches single mounting facility single center group  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                                       |
| 2.438 inches single mounting facility single center group  |
| Inductance Type:   |
| Swinging   |
| Inductance Rating:   |
| 3.00 henry single component single winding and 13.00 henry single component single winding                     |
| Body Length:   |
| 3.875 inches   |
| Body Width:  |
| 2.625 inches   |
| Body Height:   |
| 4.375 inches   |
| Winding Quantity:  |
| 1 single component   |
| Inclosure Type:  |
| Open   |
| Mounting Facility Quantity:  |
| 4 single group   |
| Mounting Method:   |
| Threaded stud single group   |
| Rating Method:   |
| Electrical single component single winding   |
| Thready Qty Per Inch (tpi):  |
| 32 single group  |
| Thread Size:   |
| 0.164 inches single group  |
| Winding Operating Current:   |
| 30.0 milliamperes dc single component single winding and 300.0 milliamperes dc single component single winding |
| Dc Resistance Rating In Ohms:  |
| 40.000 single component single winding   |
| Thread Series Designator:  |
| Unc single group   |
| Terminal Type And Quantity:  |
| 2 tab, solder lug  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 5950-00-646-2901

Reactor - Page 2 of 2



| em |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |

No

Fiig:

A058b0