Audio Frequency Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-646-3067

| Not | iability Indicator: |
|------|--|
| | nter To Center Distance Between Mounting Facilities Parallel To Length: |
| | 75 inches single mounting facility single center group |
| | nter To Center Distance Between Mounting Facilities Parallel To Width: |
| | 75 inches single mounting facility single center group |
| | insformer Function: |
| | tput |
| | bedance Rating In Ohms: |
| - | 0.0 single component single primary |
| | quency Rating: |
| | 0.0 hertz and 20.0 kilohertz single component |
| | mary To Secondary Turn Ratio: |
| | 8 to 1 single component |
| | dy Length: |
| 2.6 | 56 inches |
| Bo | dy Width: |
| 2.0 | 94 inches |
| Bo | dy Height: |
| 2.2 | 34 inches |
| Inc | losure Type: |
| Ful | ly enclosed |
| Мо | unting Facility Quantity: |
| 6 si | ingle group |
| Мо | unting Method: |
| Fla | nge and unthreaded hole single group |
| Wir | nding Function And Quantity: |
| 1 p | rimary and 1 secondary single component |
| Spe | ecial Features: |
| Cas | se metal material; mtg by two rows of three holes ea spaced 1.312 in. C to c in ro |
| Ter | minal Type And Quantity: |
| 5 ta | ab, solder lug |
| She | elf Life: |
| N/a | |
| Uni | it Of Measure: |
| | |
| Dei | militarization: |
| No | |
| Fiiç |]: |
| ۵۵۴ | 58b0 |