

View Online at <https://aerobasegroup.com/nsn/5950-00-646-3234>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.250 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.812 inches

Body Width:

3.250 inches

Body Height:

5.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

475.0 milliamperes ac single component single secondary

Winding Operating Voltage:

6.70 dc volts single component all primary and 12.20 dc volts single component all primary and 17.70 dc volts single component all primary and 24.40 dc volts single component all primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

7 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0