

View Online at <https://aerobasegroup.com/nsn/5950-00-646-4042>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

3.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.585 inches single mounting facility single center group and 2.615 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.205 inches single mounting facility single center group and 1.235 inches single mounting facility single center group

Overall Height:

2.372 inches

Overall Width:

3.000 inches

Mounting Hole Diameter:

0.203 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

6 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

3.5 amperes ac single component 1st secondary

Winding Operating Voltage:

6.30 ac volts single component 1st secondary

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0