

View Online at <https://aerobasegroup.com/nsn/5950-00-646-4382>

**Reliability Indicator:**

Not established

**Impedance Rating In Ohms:**

750.0 single component all secondary

**Frequency Rating:**

300.0 hertz single component and 3.5 kilohertz single component

**Primary To Secondary Turn Ratio:**

1 to 5 single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

Between 1.985 inches and 2.015 inches

**Body Outside Diameter:**

Between 1.454 inches and 1.484 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Distance Between Mounting Facility Centers:**

1.047 inches single mounting facility single center group and 1.077 inches single mounting facility single center group

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thread Size:**

0.138 inches single group

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

7 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0