NSN 5950-00-646-4509

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-646-4509

D	ام	ia	h	ii	i٤٠	, 1	ın	ч	i	са	4	_	r	
к	еı	ıα	D	Ш	IU	7 I	Ш	u	ı	Ca	τ	U	Г	

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.985 inches single mounting facility single center group and 3.015 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.422 inches single mounting facility single center group and 2.452 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 4.187 inches and 4.312 inches

Body Width:

Between 3.812 inches and 3.937 inches

Body Height:

Between 3.250 inches and 3.375 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

20.0 amperes ac single component single secondary

Winding Operating Voltage:

6.30 ac volts single component single secondary

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0