NSN 5950-00-646-5525

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-646-5525
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.906 inches single mounting facility single center group
Frequency Rating:
380.0 hertz and 1.0 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to core and brought out to terminal single component
Body Length:
3.938 inches
Body Width:
3.688 inches
Body Height:
4.188 inches
Inclosure Type:
Partially enclosed, double shell
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange and unthreaded hole single group
Winding Function And Quantity:
1 primary and 1 secondary single component
Winding Operating Current:
120.0 milliamperes dc single component single secondary
Winding Operating Voltage:
6.00 ac kilovolts single component single secondary
Special Features:
Case metal material; shield w/solder lug type terminal
Terminal Type And Quantity:
9 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
NI-

No

Fiig:

A058b0