## NSN 5950-00-646-5539

Current Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-646-5539

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 7.000 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 3.000 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Body Length:  |
| 16.500 inches   |
| Body Width:   |
| 8.000 inches  |
| Body Height:  |
| 7.250 inches  |
| Installation For Which Designed:  |
| Indoor nonportable  |
| Inclosure Type:   |
| Open  |
| Mounting Facility Quantity:   |
| 4 1st group   |
| Mounting Method:  |
| Flange and unthreaded hole single group                                   |
| Winding Function And Quantity:  |
| 1 primary and 1 secondary single component                                |
| Winding Operating Current:  |
| 5.0 amperes ac single component single secondary                          |
| Winding Operating Voltage:  |
| 1.00 ac kilovolts single component single primary                         |
| Terminal Type And Quantity:   |
| 2 wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A058b0  |