## NSN 5950-00-647-0870

Power Transformer - Page 1 of 2

Reliability Indicator:

Not established



View Online at https://aerobasegroup.com/nsn/5950-00-647-0870

| Overall Length:   |
|---|
| 5.060 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.062 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 3.312 inches single mounting facility single center group                 |
| Overall Height:   |
| 5.500 inches  |
| Overall Width:  |
| 4.310 inches  |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Winding Shielding Method:   |
| Internal shield grounded to inclosure and core single component           |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component               |
| Thready Qty Per Inch (tpi):   |
| 20 single group   |
| Thread Size:  |
| 0.250 inches single group   |
| Winding Operating Current:  |
| 500.0 milliamperes ac single component single secondary                   |
| Winding Operating Voltage:  |
| 700.00 ac volts single component single secondary                         |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 6 standoff insulator  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

## NSN 5950-00-647-0870

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0