# NSN 5950-00-647-3584

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-647-3584

# **Reliability Indicator:**

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

2.485 inches single mounting facility single center group and 2.515 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.047 inches single mounting facility single center group and 2.077 inches single mounting facility single center group

# **Inductance Type:**

Fixed

#### **Inductance Rating:**

1.00 henry single component single winding

#### Frequency Rating:

1.4 kilohertz single component

#### **Body Length:**

Between 3.297 inches and 3.327 inches

#### **Body Width:**

Between 2.797 inches and 2.827 inches

#### **Body Height:**

Between 2.485 inches and 2.515 inches

# **Maximum Operating Temp:**

170.0 degrees celsius

# **Winding Quantity:**

1 single component

#### **Inclosure Type:**

Fully enclosed

# **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded hole single group

#### **Rating Method:**

Electrical single component single winding

#### **Thread Size:**

0.190 inches single group

# **Winding Operating Current:**

600.0 milliamperes dc single component single winding

# Dc Resistance Rating In Ohms:

29.000 single component single winding

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

2 turret

#### Shelf Life:

N/a

# NSN 5950-00-647-3584

Reactor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0