

View Online at <https://aerobasegroup.com/nsn/5950-00-647-3624>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.219 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

4.250 inches

Body Width:

3.750 inches

Body Height:

4.625 inches

End Application:

Guided missile, intercept

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

2.6 amperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

230.00 ac pounds per hour wet single component single primary

Special Features:

Weapon system essential

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0