

View Online at <https://aerobasegroup.com/nsn/5950-00-647-5035>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

4.500 inches

Body Outside Diameter:

3.719 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange and unthreaded hole single group

Winding Function And Quantity:

1 primary and 3 secondary single component

Winding Operating Current:

6.0 amperes ac single component 3rd secondary

Winding Operating Voltage:

6.30 ac volts single component 3rd secondary

Special Features:

The center tap of 600 v 0.1 amp winding and one end of 6.3 v 6 amp winding are grounded to case and brought out to two separate terminals

Terminal Type And Quantity:

9 standoff insulator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0