

View Online at <https://aerobasegroup.com/nsn/5950-00-647-5060>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.062 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.313 inches single mounting facility single center group

Frequency Rating:

54.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

5.062 inches

Body Width:

4.312 inches

Body Height:

6.812 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Voltage:

98.00 ac volts single component 3rd secondary and 158.00 ac volts single component 3rd secondary and 728.00 ac volts single component 3rd secondary and 788.00 ac volts single component 3rd secondary and 886.00 ac volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0