

View Online at <https://aerobasegroup.com/nsn/5950-00-647-5064>

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.938 inches single mounting facility single center group

Frequency Rating:

47.0 hertz single component and 1.8 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

6.938 inches

Body Width:

6.125 inches

Body Height:

5.969 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Special Features:

Case metal material, 0.812 in. O/a h of terminals, primary winding 125 v rating w/taps at 105 v and 115 v, secondary windings rated 5 v at 4 amp, 6.3 v at 3.7 amp, 6.4 v at 7.5 map, 30 v at 1.05 amp, 1.26 kv at 325 ma w/center tap

Terminal Type And Quantity:

15 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0