## NSN 5950-00-647-5168

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-647-5168

Poliobility Indicator
Reliability Indicator: Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.750 inches single mounting facility single center group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
5.000 inches
Body Width:
4.125 inches
Body Height:
6.000 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 3 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
8.0 amperes ac single component 1st secondary
Winding Operating Voltage:
6.30 ac volts single component 1st secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
10 standoff insulator
Shelf Life:
N/a
Unit Of Measure:

## NSN 5950-00-647-5168

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

