## **NSN 5950-00-647-5199**Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-00-647-5199             |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.000 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 3.000 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Winding Shielding Method:   |
| Internal shield grounded to inclosure single component                    |
| Body Length:  |
| 4.500 inches  |
| Body Outside Diameter:  |
| 3.625 inches  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Flange and unthreaded hole single group                                   |
| Winding Function And Quantity:  |
| 1 primary and 3 secondary single component                                |
| Winding Operating Current:  |
| 4.0 amperes ac single component 3rd secondary                             |
| Winding Operating Voltage:  |
| 6.30 ac volts single component 3rd secondary                              |
| Terminal Type And Quantity:   |
| 11 tab, solder lug  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |

Fiig: A058b0