NSN 5950-00-647-5300

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-647-5300

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.580 inches single mounting facility single center group and 2.610 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.110 inches single mounting facility single center group and 2.140 inches single mounting facility single center group

Frequency Rating:

54.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 3.437 inches and 3.562 inches

Body Width:

Between 2.937 inches and 3.062 inches

Body Height:

Between 4.750 inches and 4.875 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

650.0 milliamperes ac single component 1st secondary

Winding Power Rating:

4.09 volts-amperes single component 1st secondary

Winding Operating Voltage:

6.30 ac volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-00-647-5300

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0