

View Online at <https://aerobasegroup.com/nsn/5950-00-647-5308>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

5.000 inches

Body Width:

4.280 inches

Body Height:

5.380 inches

Maximum Operating Temp:

125.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Voltage:

115.00 ac volts single component single primary

Special Features:

1 primary; 6 secondaries

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

17 standoff insulator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0