## NSN 5950-00-647-5315

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-647-5315

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 3.562 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 3.562 inches single mounting facility single center group Frequency Rating: 50.0 hertz single component or 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 4.375 inches Body Width:
Center To Center Distance Between Mounting Facilities Parallel To Length: 3.562 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 3.562 inches single mounting facility single center group Frequency Rating: 50.0 hertz single component or 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 4.375 inches Body Width:
<ul> <li>3.562 inches single mounting facility single center group</li> <li>Center To Center Distance Between Mounting Facilities Parallel To Width:</li> <li>3.562 inches single mounting facility single center group</li> <li>Frequency Rating:</li> <li>50.0 hertz single component or 60.0 hertz single component</li> <li>Input-output Phase Relationship:</li> <li>Single phase to single phase single component</li> <li>Winding Shielding Method:</li> <li>Internal shield grounded to inclosure and core single component</li> <li>Body Length:</li> <li>4.375 inches</li> <li>Body Width:</li> </ul>
Center To Center Distance Between Mounting Facilities Parallel To Width: 3.562 inches single mounting facility single center group Frequency Rating: 50.0 hertz single component or 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 4.375 inches Body Width:
<ul> <li>3.562 inches single mounting facility single center group</li> <li>Frequency Rating:</li> <li>50.0 hertz single component or 60.0 hertz single component</li> <li>Input-output Phase Relationship:</li> <li>Single phase to single phase single component</li> <li>Winding Shielding Method:</li> <li>Internal shield grounded to inclosure and core single component</li> <li>Body Length:</li> <li>4.375 inches</li> <li>Body Width:</li> </ul>
Frequency Rating: 50.0 hertz single component or 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 4.375 inches Body Width:
50.0 hertz single component or 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 4.375 inches Body Width:
Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 4.375 inches Body Width:
Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 4.375 inches Body Width:
Winding Shielding Method: Internal shield grounded to inclosure and core single component Body Length: 4.375 inches Body Width:
Internal shield grounded to inclosure and core single component Body Length: 4.375 inches Body Width:
Body Length: 4.375 inches Body Width:
4.375 inches Body Width:
Body Width:
-
1 2EQ inches
4.250 inches
Body Height:
4.781 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 2 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.190 inches single group
Winding Operating Current:
4.75 amperes ac single component 2nd secondary
Winding Operating Voltage:
2.50 ac volts single component 2nd secondary
Thread Series Designator:
Unf single group
Terminal Type And Quantity:
7 standoff insulator
Shelf Life:
N/a
Unit Of Measure:
-

## NSN 5950-00-647-5315

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

