# NSN 5950-00-647-5675

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-647-5675

# **Reliability Indicator:**

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

# **Overall Height:**

5.094 inches

#### **Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

# Input-output Phase Relationship:

Single phase to single phase single component

# Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

# **Body Length:**

# 3.750 inches

**Body Width:** 

3.500 inches

#### Body Height:

4.250 inches

# Maximum Operating Temp:

34.0 degrees celsius

# Inclosure Type:

Hermetically sealed

# **Mounting Facility Quantity:**

4 single group

# Mounting Method:

Threaded stud single group

# Winding Function And Quantity:

1 primary single component and 2 secondary single component

# Thready Qty Per Inch (tpi):

32 single group

# **Thread Size:**

0.190 inches single group

# Winding Operating Current:

8.5 amperes ac single component 1st secondary

# Winding Operating Voltage:

6.30 ac volts single component 2nd secondary

# **Thread Series Designator:**

Unf single group

# **Terminal Type And Quantity:**

6 standoff, solder lug and 1 tab, solder lug

# NSN 5950-00-647-5675

Power Transformer - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0

