NSN 5950-00-647-6184

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-647-6184

| Reliability Indicator: |
|----------------------------------|
| Not established |
| Center To Center Distance Bety |
| 1.250 inches single mounting fac |

ween Mounting Facilities Parallel To Length:

cility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.125 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.781 inches

Body Width:

1.781 inches

Body Height:

2.031 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

8 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

0.1 amperes ac single component single secondary

Winding Operating Voltage:

6.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5950-00-647-6184Power Transformer - Page 2 of 2



Fiig:

A058b0