

View Online at <https://aerobasegroup.com/nsn/5950-00-647-6219>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.250 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

5.500 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

4.625 inches

**Body Width:**

4.375 inches

**Body Height:**

6.125 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange and unthreaded hole single group

**Winding Function And Quantity:**

1 primary and 4 secondary single component

**Winding Operating Current:**

6.5 amperes ac single component 3rd secondary

**Winding Operating Voltage:**

6.50 ac volts single component all secondary

**Special Features:**

The 6.5 volt 24 amp winding has 2 common terminals for ea end of winding

**Terminal Type And Quantity:**

16 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0