NSN 5950-00-647-6479

Reactor - Page 1 of 2

Reliability Indicator:

Not established



View Online at https://aerobasegroup.com/nsn/5950-00-647-6479

Center To Center Distance Between Mounting Facilities Parallel To Length:
6.125 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
5.250 inches single mounting facility single center group
Overall Height:
6.000 inches
Inductance Type:
Fixed
Inductance Rating:
10.00 henry single component single winding
Frequency Rating:
60.0 hertz single component
Body Length:
7.375 inches
Body Width:
6.500 inches
Body Height:
5.250 inches
Maximum Operating Temp:
65.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Rating Method:
Electrical single component single winding
Thready Qty Per Inch (tpi):

Winding Operating Current:

0.250 inches single group

 $550.0 \ \mbox{milliamperes} \ \mbox{dc} \ \ \mbox{single component single winding}$

Dc Resistance Rating In Ohms:

47.000 single component single winding

Thread Series Designator:

Unc single group

20 single group

Thread Size:

NSN 5950-00-647-6479

Reactor - Page 2 of 2



Termina	I Type	And (Quantit	٧.
	11 1 1 1 1 1 1	Allu '	wuanni	ν.

2 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0