## NSN 5950-00-647-6660

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-647-6660

| Reliability Indicator:                                                    |
|---------------------------------------------------------------------------|
| Not established                                                           |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.000 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.875 inches single mounting facility single center group                 |
| Inductance Type:                                                          |
| Fixed                                                                     |
| Inductance Rating:                                                        |
| 19.00 henry single component single winding                               |
| Body Length:                                                              |
| 2.938 inches                                                              |
| Body Width:                                                               |
| 2.562 inches                                                              |
| Body Height:                                                              |
| 3.750 inches                                                              |
| Winding Quantity:                                                         |
| 1 single component                                                        |
| Inclosure Type:                                                           |
| Hermetically sealed                                                       |
| Mounting Facility Quantity:                                               |
| 4 single group                                                            |
| Mounting Method:                                                          |
| Threaded stud single group                                                |
| Rating Method:                                                            |
| Electrical single component single winding                                |
| Thready Qty Per Inch (tpi):                                               |
| 32 single group                                                           |
| Thread Size:                                                              |
| 0.138 inches single group                                                 |
| Winding Operating Current:                                                |
| 60.0 milliamperes dc single component single winding                      |
| Dc Resistance Rating In Ohms:                                             |
| 420.000 single component single winding                                   |
| Thread Series Designator:                                                 |
| Unc single group                                                          |
| Terminal Type And Quantity:                                               |
| 2 standoff, solder lug                                                    |
| Shelf Life:                                                               |
| N/a                                                                       |

--

**Unit Of Measure:** 

## NSN 5950-00-647-6660

Reactor - Page 2 of 2



| _  |    | •• | • • |     |     |   |    |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш  | 112 | rız | 211 | n | ٠. |
|    |    |    |     |     |     |   |    |

No

Fiig:

A058b0