NSN 5950-00-647-6679

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-647-6679

To Length:

To Width:

| Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel 3.688 inches single mounting facility single center group |
|--|
| Center To Center Distance Between Mounting Facilities Parallel 3.688 inches single mounting facility single center group |
| 3.688 inches single mounting facility single center group |
| |
| |
| Center To Center Distance Between Mounting Facilities Parallel 2.750 inches single mounting facility single center group |
| |
| Mounting Hole Diameter: |
| 0.141 inches single group |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 4.625 inches |
| Body Width: |
| 4.062 inches |
| Body Height: |
| 4.312 inches |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Winding Operating Current: |
| 1.0 amperes ac single component 1st secondary |
| Winding Operating Voltage: |
| 310.00 ac pounds per hour wet single component 2nd secondary |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A058b0