# NSN 5950-00-647-6690

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-647-6690

# Reliability Indicator:

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

# **Overall Height:**

5.000 inches

#### **Frequency Rating:**

55.0 hertz single component and 65.0 hertz single component

# Input-output Phase Relationship:

Single phase to single phase single component

# Winding Shielding Method:

Internal shield grounded to inclosure and core single component

#### **Body Length:**

Between 3.437 inches and 3.562 inches

#### **Body Width:**

Between 2.937 inches and 3.062 inches

#### **Body Height:**

Between 3.750 inches and 3.875 inches

# Maximum Operating Temp:

105.0 degrees celsius

# Inclosure Type:

Hermetically sealed

#### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded hole single group

# Winding Function And Quantity:

1 primary single component and 2 secondary single component

#### Thready Qty Per Inch (tpi):

32 single group

#### **Thread Size:**

0.164 inches single group

#### Winding Operating Current:

8.0 milliamperes ac single component 2nd secondary

# Winding Operating Voltage:

2.10 ac kilovolts single component all secondary

#### **Thread Series Designator:**

Unc single group

# Terminal Type And Quantity:

6 standoff insulator

# NSN 5950-00-647-6690

Power Transformer - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0

