

View Online at <https://aerobasegroup.com/nsn/5950-00-647-6765>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.750 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

6.781 inches

Body Width:

5.281 inches

Body Height:

7.125 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

560.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

575.00 ac volts single component 1st secondary

Special Features:

The center tap of the 1.100 v winding and the center tap of the 575 v winding have one common terminal

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 solder stud and 1 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0